

"HYDRAULIC MACHINE OF BOOSTING
AND RECOVERY OF THE LIQUID IN INTERNAL MOVEMENTS IN THE
ELECTRIC ENERGY PRODUCTION"

This patent of invention
5 refers to a machine specially developed for production of
electric power, which through the movement of one or more
cylinders, depending on the size of the machine, embedded in
one sleeve or more exerts its movement upwards and
downwards. Said sleeve and the cylinder are inside the tank
10 or water column and inside it perform their movements. In
the sleeve there is a ring that seals the exit of the water
or other liquids from the tank to outside. And also allows
the transference of the liquid from the sleeve to the tank
number one. This ring when leaned against the wall allows
15 the cylinder to be displaced from down to up and generates
an empty space in the interior of its sleeve that is
immediately occupied by the water or other liquid through
the opening of the plug or valve existent in the recovery
box that was used in the movement of the rotor. Note that
20 this box is higher than the level of the sleeve where is the
cylinder to thus allow the internal invasion of the water as
result of the difference of level. Closed the plug of the
water box and opened the ring, the cylinder makes the
inverse course and exerts the boosting of the water or other
25 liquids through the opening of the ring, which makes
possible to execute new movements in high speed in the
transference of the liquid from the sleeve to the tank
number one. But, everything becomes easy, the liquid

transference is immediate and with little effort, as the cylinder and the chamber are inside the tank one liquid and occupy part of this space. It should be highlighted here the materials to be used in the strains to be executed through a

5 central axle that is moved by a motor that may be electrical or of other type, in this axle are tied two steel cables with tying in opposite directions, one of the cable holds the central cylinder of the machine, the other cable holds a weight outside the machine and they form a swing between the

10 internal and the external weights, when the cylinder cable goes up the cable of the external weight goes down. When the external weight goes up the cylinder goes down. These movements are well balanced and make the movement of the machine with low energy consumption. In the ring and in the

15 plug or valve it is used pneumatic cylinders due to the need of speed in the production of great volume of liquid in movement. All these movements are duly commanded by sensors installed in several points of the machine. The Figure (1) shows the machine as a whole, (1) in the tank or water

20 column or other liquids this height varies according to the volume of the water that is required to rotate the rotor. Note that the machine may be of big dimension, for such, it is necessary to use more than one cylinder, the tank may be one or more, depending on the necessity, (2) level pipe of

25 the water from the box to the column, when the cylinder goes up the water immediately invades the space left by the cylinder, (3) water box that receives the flow of the water movement in the turbine rotor and through its level it is

possible to recover it and transmit it through the pipe to the cylinder sleeve, (4) cylinder sleeve, this sleeve when the ring leans against it eliminates the flowing of the water out of the interior of the tank to outside and allow
5 us to make the recovery of the liquid that was used in the turbine rotor through the empty space left by the cylinder when it goes up, (5) cylinder that goes up and down, when it goes up with the ring closed it allows the recovery of the water or of the liquids. When it goes down with ring open
10 and the plug closed it discharges the liquid from the interior of the sleeve to the interior of the mother-tank and so raises the water level and causes its falling on the rotor (6) the sealing ring of the cylinder sleeve to the tank, when the cylinder is open it is ready to start its
15 descent, when the cylinder is closed it is ready to start its ascent, (7) pneumatic cylinder, this cylinder has the function of opening and closing the sealing ring, (8) pneumatic cylinder, this cylinder has the same function of the cylinder seven, (9) pneumatic cylinder, this cylinder
20 has the function of opening the plug or valve, depending on what is possible to be faster in the sealing of the passing of the water of the pipe recovery box , (10) plug that makes the sealing of the passing of the water or other liquids, (11) left side cylinder guide-stem, (12) right side cylinder
25 guide-stem, (13) external weight that makes the balance between the internal cylinder and the external weight, (14) pulley fixed to the axle with steel cable that sustains the external weight with inverted tieing, when the cylinder goes

down the weight goes up, (15) pulley fastened to the central axle that through an electric motor or other it is possible to spin the axle and impart movements to the machine, (16) electric motor that through a belt is interconnected to the central axle of the machine and exerts the movement of the same, (17) motor supporting table, (18) supporting table of the pneumatic cylinder that gives the movement to the plug, (19) stem of fixing of the machine to the pipe, (20) the machine fixing stem has the same function of the nineteenth, (21) stem of fixing of the pipe to the ground, (22) stem of fixing of the mother-pipe to the ground, (23) stem of holding of the pipe to the ground, (24) pulley fixed to the central axle where is tied a steel cable that when put in movement exerts the function of making the cylinder go up and go down, (25) cable of tieing of the pulley to the cylinder, (26) central axle of the machine where the cables that are fastened to the pulleys rotate in inverse directions, (27) turbine or rotor that through the beating of the water transfers the movement to the generator and in this manner makes possible the production of electric energy, (28) pipe of conduction of the water or other liquid to the turbine rotor, (29) sealing ring of the machine central cylinder, (31) it should be emphasized that the cylinder that goes up and down according to figure, a cylinder five that makes the up and down movement also can be made as the (Figure 2) will show us, also may be constructed in form of open glass, what facilitates very much, as long as its liquid is displaced by another, (32)

cylinder that is stopped and with movement of the cylinder in form of glass, from down to up is made the displacement of the liquid when the cylinder in glass penetrates in the cylinder that is stopped. It should be emphasized that the
5 position (33) of the pulleys are fixed in the lateral of the cylinder in form of glass and not to the center.